

## General description

類號

總號

CH

Type of machine	CH-3	CH-5S	CH-5L	CH-6S	CH-6L	CH-6LL
Min. & Max. cut-off dia	0.8~3	2~5	2~5	3~6.35	3~6.35	3~6.35
Min. & Max. cut-off length of shank	34	45	69	63	89	128
Max. cutoff shank length of blank	3~22	6~25.4	6~50.8	8~38	8~64	25~102
Main dia	∅25x34L	∅30x45L	∅30x65L	∅38x55L	∅38x75L	∅38x110L
Cut-off die dia	∅15x20L	∅20x30L	∅20x30L	∅25x35L	∅25x35L	∅25x35L
Distance of main dia & cut-off dia	24	30	30	36	36	40
#1 punch dia	∅22x44L	∅27x58L	∅27x58L	∅35x74L	∅35x74L	∅35x74L
#2 punch dia	∅18x40L	∅25x52L	∅25x52L	∅35x67.5L	∅35x67.5L	∅35x67.5L
Distance of #1 & #2 pnuch	24	30	30	41	41	41
Main slider stroke	44	60	84	80	106	146
P.K.O. stroke	4	6.5	10	8	10	12
K.O. stroke	22	26	51	38	64	102
Main motor (HP)	2(3)	7.5	5	7.5	7.5	7.5
Max. out-put (pcs/min)	300	250	200	200	160	110
Net weight (tons)	650	1,300	1,400	2,300	2,500	3,000
Floor space ( L. x W. x H. ) (Without wire straightener)	1426x818x640	1903x990x997	1903x990x997	1078x1041x1058	1078x1041x1058	2013x1041x1223

(Dimension : mm)